



SAS QUICK COUPLER FOR WHEEL LOADERS



SWITCH ATTACHMENTS IN SECONDS NOT HOURS

INCREASE PRODUCTIVITY:

- SAS COUPLERS go from design-manufacturing to completion in 2 weeks or less.
- INCREASED VISIBILITY through coupler preventing operator damage to product.
- ZERO DOWN TIME, SAS quick coupler made of High Strength Steel.
- INTERFACE allows use of multiple manufactures attachments.

ENGINEERED & BUILT FOR DURABILITY:

- MAXIMUM LIFT capacity of machine maintained by shorting the distance of attachment from lift arms of machine.
- COMPUTERIZED STRESS analysis done by Mechanical Engineers during design process.
- COUPLER WIDTH designed to align closely with OEM lift arms of machine efficiently transferring force from attachment to machine, eliminating points of stress & fatigue.
- MAINTENANCE FREE hydraulic cylinder is securely enclosed for years of service.


SAS FORKS are trusted to handle over 12 Million lifts annually!

BEST SUITED FOR:


- Standard couplers fit 1 to 4 yard capacity wheel loaders with curb weight of 16,000 to 45,000 lb.
Custom coupler solutions available for larger wheel loaders, forklifts or telehandlers.
- Wheel loader with existing auxiliary hydraulic function.
Optional independent auxiliary hydraulic pump available to operate coupler cylinder.

SAS QUICK COUPLER FOR WHEEL LOADERS


3 Pin Mount Quick Coupler



4 Pin Mount Quick Coupler



Tool Attachment Ribs



Deep Back Thin Back

Electric Hydraulic Pump Kit

- √ Qty 1 Electric Pump w/reservoir 2000PSI
Remote wired pendent control
(Overall size: 8" tall x 17" long x 6" deep)
- √ Qty 2- 30' 3/8" diameter 3,000PSI hose
w/fittings installed :Female JIC37

Quick Coupler (no hydraulic pump, hoses, wires, or pins)

Designed and machined to attach directly to your pin configuration.

- 3 Pin Mount
- 4 Pin Mount

Tool Interface:

- Standard 'SAS-Euro'-ISO-Volvo (L45-L120) Loader 16-45,000 lb.
- Custom Coupler Make _____ Model _____ Series _____

Standard Items Included:

- √ Precision machined solid welded quick coupler frame painted black
- √ Upper solid steel mounting shaft & 2 hardened lower locking pins
- √ Internal hydraulic cylinder (Max 5,000 PSI)
- √ External fittings to attach your hydraulic source
- √ Operator & Safety Manual
- √ 1 year Limited Warranty against defective weldment workmanship.

Optional Items: (Optional items to be itemized on price quote)

- Pins: Installation pins: Pin proof required Qty _____

Contact:

SAS Forks
133 Center Drive Hwy 54 - PO Box 260
Luxemburg, WI 54217-0260 U.S.A.
Phone: 877-727-3675 Fax: 920-845-2309

Email: sales@sasforks.com

Website: www.sas-rail.com

0-MM-0 BWQ#

CAPACITY & DESIGN CONSIDERATIONS

Use: Quarry Construction Salvage _____

(Typical 'SAS-Euro' Quick Coupler wt 1,600 lb.) Load Center

Max Load desired? _____ lb. kg. @ _____

Machine capacity? _____ lb. kg. @ _____

Breakout force? _____ lb. kg.

MACHINE: Make _____ Model _____



SCAN QR CODE FOR MORE INFORMATION

